

Specification 特性:

- For Motorcycle
- High sensitive and stable electronic timing
- Standard Terminals, usage and replacement easily with ticking sound

适用于摩托车;
具有高灵敏性和稳定性的电子计时;
标准终端, 使用更换方便, 使用时有滴答声.

Ordering Guide 订货指南

Example 示例	KKA-SG152B	-012	J
Type 闪光器型号			
Coil Volt. 线圈电压	012:12VDC		
Output Pins 引出脚形式	J:3 Pin		

Specification 性能参数

Contact 触点	Contact Forms 触点形式	1H
	Contact Material 触点材料	银合金
	Contact Load 触点负载	10A
	Contact Switching Current 触点切换电流	10A
	Contact Switching Voltage 触点切换电压	12V
Rating 参数	Rated Voltage 额定电压	12VDC/24VDC
	Rated Current 额定电流	10A
	Operating Voltage 工作电压	11VDC ~ 15VDC
	Test Voltage 试验电压	13VDC ± 0.2DC
	Test Temperature 试验温度	20°C ± 2°C
	Switch Load 切换负载	0.1W ~ 150W (0.02A ~ 20A)
	Coil Power 线圈功率	0.36W
	Max. Power 最大功率	150W
	Flashing Frequency 闪光频率	60 ~ 120 times per minute
	Duty Ratio 占空比	30% ~ 70%
	Operating Temperature 工作温度	-40°C ~ +80°C
Expected Life 寿命	400 Working hours 400 工作小时	
Weight 重量	25g	



Dimensions 外型尺寸

